

Imbotex

ultimate insulations









Via Molini, 26 – S. Croce Bigolina 35013 Cittadella (PD)

Tel. +39(0)499445022 – Fax: +39(0)499445068

e-mail: info@imbotex.it – P. IVA: IT00277480281

SCHEDA TECNICO-INFORMATIVA PRODOTTO/PRODUCT INFORMATION SHEET

TENCEL PAD

COMPOSIZIONE/ COMPOSITION	85% Tencel (LY) 15% Low-melting PLA Ingeo staple fiber (PLA)
GRAMMATURA/ WEIGHT FOR UNIT AREA [g/m ²]	100 - 200 gr/sm
TRATTAMENTO/ PROCESSING	Cardatura - faldatura - termolegatura Carding - Cross-lapping - Thermobonding
SCRIM/LAYER	1 scrim 14 gr/sm (PP)
SETTORI DI IMPIEGO/ USE	Imbottiture per abbigliamento. Insulations for apparel.
FORNITURA E IMBALLAGGIO / SUPPLY AND PACKING	Rotoli con altezza 152 cm. Imballaggio standard rotoli: tubo di cartone e sacco in polietilene. Tolleranza su lunghezza prodotto: -0/+1000 mm Tolleranza su larghezza prodotto: ±5 mm Tolleranza su peso prodotto al m ² : ± 7% In rolls, width 152 cm. Rolls standard packing: Cardboard tube and polyethylene-film bag Tolerance on product length: 0/ +1000 mm Tolerance on product width: ± 5 mm Tolerance on weight per m ² : ± 7%
 Tencel Pad is made with macro and micro fibers; we suggest to use down proof fabrics for the lining and the shell.	
NOTES DELIVERY TERMS: 10 days from order M.O.Q.: 500 lmt      	PRODUCT MADE IN ITALY 

Cittadella, 02/04/2021